



# O' Tannenbaum 2.5 – Product Specification



M 1:200



## HodgePodge – A variety of study and durable sport and play elements

HodgePodge is a clever and versatile combination of play equipment and climbing structures that can be used anywhere and for numerous activities. Climbing trees, a Wasp's nest, Volleyball nets for sporting activities, cable rides for fun and excitement.

### O' Tannenbaum 2.5 – At a glance.

Product Family:	<b>HodgePodge</b>	Number of Foundations:	<b>1 pc.</b>
Item Number:	<b>90.340.045</b>	Concrete Volume C20/C25:	<b>1.2 m<sup>3</sup> (42.4 ft<sup>3</sup>)</b>
Children's Age:	<b>3+</b>	Number of skilled installers required:	<b>3</b>
Fall Height (DIN EN 1176):	<b>0.50 m (1'-8")</b>	Installation Time without foundation:	<b>6 hours</b>
Length x Width x Height:	<b>2.1 m x 2.1 m x 2.5 m (6'-9" x 6'-9" x 8'-3")</b>	Dimensions of largest part:	<b>Ø 0.1 m x 3.4 m (0'-4" x 11'-2")</b>
Protective Surfacing Area (DIN EN 1176):	<b>5.1 m x 5.1 m</b>	Weight of heaviest part:	<b>75 kg (165.3 lbs)</b>
Protective Surfacing Area (ASTM 1487):	<b>5.7 m x 5.7 m (18'-9" x 18'-9")</b>	Shipping Volume:	<b>1.7 m<sup>3</sup> (60.0 ft<sup>3</sup>)</b>
Minimum space required DIN EN 1176:	<b>20.0 m<sup>2</sup></b>	Spare part guarantee:	<b>Lifelong</b>
Minimum space required ASTM 1487:	<b>25.6 m<sup>2</sup> (275.6 sf)</b>	Certificate according to EN 1176:	<b>No.: Z2.16.01.10256.257 TÜV Product Service</b>

## Technical Data.

The following text can also be used for tenders.

### Central mast:

Steel post 133 mm (5 ¼"), wall thickness 6.3mm (1/4"), anti-corrosion treatment and color finish: sandblasting and solvent-free zinc-/ epoxy-/ polyester-process.

### Mast node:

Frameworkx-aluminum ball connector; Ø 250 mm (9-13/16"); anti-corrosion treatment and color finish: sandblasting and solvent-free zinc-/ epoxy-/ polyester-process; with inlying net tensioning system, secured with a durable EPDM-cap.

### Rubber membrane:

Comprised of durable, vandal-resistant conveyor belt material.

### Ropes:

U-Rope®-round strand ropes with galvanized and covered wires: external strands with non-abrasive UV-resistant Polyester-yarn (no Polypropylene); rope-diameter Ø 16 mm (5/8").

### Outer rings:

Bended Frameworkx-steel pipes, Ø 48.3 mm (1 7/8"); anti-corrosion treatment and color finish: sandblasting and solvent-free zinc-/ epoxy-/ polyester-process.

### Netting and suspension ropes:

rope crossing points localized by durable, drop forged aluminium-ballknots (no plastic).